

FLUORESCENT LIGHT



Model : RF-Mini
Lamp opening : ID 55mm
Power consumption : 12W
Color temperature : 5600K
Bulb Life : ≥ 2000 hours
Power : 110V or 220V



Model : RF-92
Lamp opening : ID 60mm
Power consumption : 8W

Model : RF-100
Lamp opening : ID 70mm
Power consumption : 11W
Power : 110V or 220V



Model : Everlite -208T
Aluminium Casing : 195x38x25mm
Power consumption : 11W
Fuse : 2A
Power : 220V



Model : Mini Lamp
 Day light.
 OD 82mm, Length
 115mm, 4 pins, 12W



Model : 80BDL
 Day light

Model : 80BWW
 Warm white. OD 80mm, Total
 length 10mm, 4 pins, 8W



Model : 92ADL / 100ADL
 Day light

Model : 92AWW
 Warm white. OD 92mm,
 Total length 105mm, 4 pins, 8W



Model : EKE-13629
 Halogen 21V/150W



Model : 92BDL
 Day light.
 OD 92mm, Total length
 118mm, 4 pins, 8W



Model : 85BDL
 Day light.
 OD 85mm, Total length
 132mm, 2 pins, 8W



Model : SY-BDL
 Day light.
 OD 85mm, Total length
 131mm, 4 pins, 8W



Model : 120BDL
 Day light.
 OD 120mm, 4 pins,
 12W

Replacement Bulb

FIBER OPTIC ILLUMINATOR



Model : VFO-311101
Power output : 150W
Illumination : ≥ 100K Lux
Color Temperature: 3000K
Lamp : 21V 150W halogen
Bulb Life : 200 hours
Fuse : 2A (3 x 20mm)
Dimension : 208x124x105mm
Power : 110V or 220V
Built-in : Cooling fan, high voltage
 resistance, heat relay,
 Day light filter

* Option : Filter kit (Red, blue, Green)



Fiber Optic Light Guide



Model : VFOC-321101
 Fiber optic light guide, 1 meter, Ring ID 58mm,
 Fiber Ø10mm, Connector Ø15.6mm



Model : VFOC-324101
 Fiber optic 4"x4" Back light guide,
 1 meter, Fiber Ø10mm,
 Connector Ø15.6mm

Model : VFOC-324102
 Fiber optic 2"x2" Back light guide,
 1 meter, Fiber Ø6.5mm,
 Connector Ø15.6mm



Model : VFOC-323203
 Coaxial Fiber optic light guide,
 1 meter, Fiber Ø8mm, Head
 Ø9x10mm



Model : VFOC-323101
 Single Fiber optic light guide, 450mm, Fiber
 Ø6mm, Connector Ø15.6mm, with focus lens

Model : VFOC-322101
 Double Goose Neck Fiber optic light guide,
 450mm, Fiber Ø7.1mm, Connector Ø15.6mm,
 with focus lens